SECURITY AD-A273 6	92	•					
	ITATION	N PAGE			Form Approved OM8 No. 0704-0188		
la REPONI SECUNITI CONSTITUCIO.		16 RESTRICTIVE N	MARKINGS				
Unclassified 2a. SECURITY CLASSIFICATION AUTHORITY		None 3 DISTRIBUTION/AVAILABILITY OF REPORT Distribution A: Unlimited					
N/A 2b. DECLASSIFICATION / DOWNGRADING SCHEDULE		Distribut	tion A: Uni	TWITEG			
N/A		5. MONITORING ORGANIZATION REPORT NUMBER(\$)					
4. PERFORMING ORGANIZATION REPORT NUMBER(S) DODPOPHMIR/AYD 93-029		None					
6a. NAME OF PERFORMING ORGANIZATION Packaging Division	6b. OFFICE SYMBOL (If applicable)	7a. NAME OF MO	ONITORING ORGAN	IIZATION			
6c. ADDRESS (City, State, and ZIP Code)	SMCAR-AEP	7b. ADDRESS (City	v :	33-	29981		
U.S. Army Armament Research, Development and Engineering Center Picatinny Arsenal, NJ 07806-5000		None	998				
8a. NAME OF FUNDING/SPONSORING ORGANIZATION Same as 6a	8b. OFFICE SYMBOL (If applicable) SMCAR-AEP	9. PROCUREMENT	INSTRUMENT IDE	NIIFICAI	ION NUMBER		
8c. ADDRESS (City, State, and ZIP Code)		10. SOURCE OF F	UNDING NUMBERS				
Same as 6c		PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.	WORK UNIT ACCESSION NO.		
11. TITLE (Include Security Classification) Annual retest of POP Requirements of wirebound box for small caliber ammunition packed in PAl08 Metal Container.							
12. PERSONAL AUTHOR(S) Edgardo B. Silvestre							
13a. TYPE OF REPORT 13b. TIME CO Final FROM	4. DATE OF REPORT (Year, Month, Day) 15. PAGE COUNT 931105						
16. SUPPLEMENTARY NOTATION	то	331.	103				
17. COSATI CODES	18. SUBJECT TERMS (C						
FIELD GROUP SUB-GROUP	1. Performance 2. Ammunition 1	Oriented Packaging 4. Wirebound Box Packaging 5. Packaging					
	3. PA108 Contai	iner					
19. ABSTRACT (Continue on reverse if necessary and identify by block number) This report covers the annual retest of POP Requirements of wirebound box, part No. 12590218 used as shipping container for 5.56mm small caliber ammunition. This wirebound box contains two PA108 metal containers containing 5.56mm small caliber ammunition for Squad Automatic Weapons. Tests were conducted using additional test weight in order to insure shipping container's integrity. DTIC ELECTE DECO 9 1993 E							
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT UNCLASSIFIED/UNLIMITED SAME AS RI	PT. 🔲 DTIC USERS	21. ABSTRACT SEC Unclass	ified				
22a. NAME OF RESPONSIBLE INDIVIDUAL Edgardo B. Silvestre		225. TELEPHONE (/ (201) 724-2			FICE SYMBOL IR-AEP		
DD Form 1473, JUN 86	Previous editions are o			CLASSIFIC	ATION OF THIS PAGE		

93 12 8 071

Best Available Copy

ANNUAL RETEST OF

PERFORMANCE ORIENTED PACKAGING REQUIREMENTS

OF

WIREBOUND BOX FOR SMALL CALIBER AMMUNITION

PACKED IN PA108 METAL CONTAINER DITC QUALIT

DTIC QUALITY INSPECTED 5

FOR

PACKING GROUP II
SOLID HAZARDOUS MATERIALS

Author:

EDGARDO B. SILVESTRE PACKAGING TECHNOLOGIST

Accesion For

NTIS CRA&I
DTIC TAB
Unannounced
Justification

By
Dist. ibution |

Availability Codes

Dist
Avail and | or
Special

Performing Activity

SMCAR - AEP
U. S. Army Armament Research, Development
and Engineering Center
Picatinny Arsenal, New Jersey 07806-5000

October 1993 - October 1994

FINAL

<u>Distribution Statement A.</u>
Approved for public release;
Distribution is unlimited.

PREPARED BY:

Edgardo B. Silvestre Packaging Technologist

REVIEWED BY:

James F. Zoll
Supervisory Packaging Engineer

APPRQUED BY:

Robert J. Kuper Chief, Packaging Division

INTRODUCTION

The Department of Transportation (DOT) per CFR 49, Parts 100-179, dated 1 October 91, requires that hazardous materials should be packed in a container that passes the Performance Oriented Packaging (POP) tests. Furthermore, these tests are to be repeated on an annual basis for items in production.

Wirebound box, part number 12590218, is being used as shipping container for 5.56mm small caliber ammunition. This box contains two(2) PA108 metal containers containing 5.56mm small arms ammunition for Squad Automatic Weapon. This box contains a maximum gross weight of 54 kg.

POP tests were conducted using additional weight(62 kg test weight) to insure container integrity. The tests were conducted in accordance with the referenced sections of CFR 49 and are valid only when the approved ammunition are packed in the PA108 container for the DOD(see Table). This wirebound box was tested previously and certified for 54 Kg of gross weight of Packing Group II Items. This report represents the annual retest of the wirebound box for PA108 metal container for POP certification.

TESTS PERFORMED

1. Drop Test

Section 178.603 of CFR 49 specifies that one box each should be used for each drop orientation. Five (5) boxes were used for five different orientations. Containers were tested to Packing Group II requirements.

One box each was dropped from a height of 1.2 meters (3.9 ft.) in the following orientations: flat on bottom, flat on top, flat on long-side, flat on short-side and on a corner.

2. Vibration Test

Three (3) boxes were placed on the vibrating platform and vibrated for a duration of one hour. The boxes were unrestrained except horizontally to prevent them from falling off of the platform. The peak-to-peak displacement was one inch and the frequency was 4.6 Hertz/sec. This frequency was sufficient enough to allow the package to become completely airborne, enabling a 1/16 inch (.16 cm) thick piece of strapping material to be slid underneath the package during testing.

3. Stacking Test

Section 178.606 of CFR 49 requires that the minimum height of the stack including the test sample must be 3.0 meters (10 ft). Three test samples are required.

A 3.0 meter stack height of samples is equivalent to 1,695 lbs. (771 kg) of stack weight. Three different test samples were each subjected to a stack weight of 1,695 lbs for a period of 24 hours. The samples were then inspected and examined for any damage or distortion.

PASS/FAIL (DOT CRITERIA)

A package for explosives is considered to successfully pass the drop tests if for each sample tested, no rupture of the packaging occurs.

A packaging passes the vibration test if there is no rupture or leakage from any of the packages.

A test sample passes the stacking test when no test sample leaks. No test sample may show any deterioration which could adveresly affect transportation safety or any distortion likely to reduce its strength or cause instability in stacks of packages.

TEST RESULTS

Drop Test - Result: pass, no spillage.

The first four drops did not do any damage on any of the four boxes. On the edge drop, one of the long side of the box cracked but there was no spillage.

2. Vibration Test - Result: pass, no spillage or damage.

All three boxes were removed from the platform after one hour vibration. Each of the boxes was turned on its side and inspected for any damage and leakage. The packages were all tightly intact and showed no evidence of deterioration.

3. Stacking Test - Result: pass, no evidence of distortion.

The stacking test was performed with the use of a forklift to apply a dead load of 1,695 lbs on top of each of the three boxes. Each of the boxes adequately supported the applied load. No evidence of box distortion was noted.

REMARK

Based on the successful POP testing outlined in this report, the following POP symbol:

last two digits of year packed

Quantum 4C1/Y54/S/CIU USA/DOD/AYD

shall be applied to containers manufactured in accordance with drawing 12590218 when used to package the NSN's listed in the Table from October 1993 through October 1994.

REFERENCE MATERIAL

- 1. Federal Register, "49 CFR Part 107, 1 Oct 91
- 2. Federal Specification PPP-B-585

TEST DATA

DATA

Container(Outer):

Type: Box, wirebound

Part No.: 12590218

UN Code: 4C1

Spec No.: PPP-B-585

Material: Wood

Capacity: 28.0 liters

<u>Dimensions</u>

Inside: 37.47 cm x 37.70 cm x 22.86 cm

 $(14 \ 3/4 \ in \ x \ 12 \ 7/8 \ in \ x \ 9 \ in)$

Outside: 43.18 cm x 33.97 cm x 23.81 cm

(17 in x 13 3/8 in x 9 3/8 in)

Weight(empty): 2.7 kg (6.0 lbs)

Container(inner):

Type : Box Model No : PA108

Spec No: : MIL-C-70628

Material : Metal

Capacity: 10.8 liters

Dimensions:

Inside : 30.16 cm x 17.15 cm x 20.84 cm

(11 7/8 in x 6 3/4 in x 8 13/64 in)

Outside : $32.78 \text{ cm} \times 18.53 \text{ cm} \times 22.62 \text{ cm}$

(12 29/32 in x 7 19/64 in x 8 29/32 in)

Weight : 3.0 kg (6.0 lbs)

Closure(Method/Closure): Hinged Lid

PRODUCTS:

Identification No. : See Table

UN Packing Group : II
Physical State : Solid
Amount per Container : See Table

TEST MATERIALS:

Name : Simulated Weights and Sand

Physical State : Solid

Size : 10 in x 3 in x 3 in

or 2 in dia x 7/8 in thick

or granulated sand : Twelve(12) lead weights or lead tablets Quantity

or 136 lbs

Dunnage : Polyethylene foam per PPP-C-1752 Gross Weight : 136 lbs(62 kg)

TABLE

KG/BX	%	*	5 6
LBS/BX	75	75	57
UN NO.	0012	0012	0014
23	1.48	1.48	1.4S
Type	Ball TR	Ball	Blank
HM Item	5.56mm	5.56mm	5.56mm
or NGN	1305-01-252-0153	1305-01-258-8692	1305-01-258-8694
DODIC O		A062	
Line No.	-	7	က